AMENDMENTS TO THE CLAIMS

2

- (Currently amended) A dye-sensitized photoelectric transfer device comprising:

 a semiconductor layer containing titania nanotubes; and
 a sensitizing dye retained by the titania nanotubes, wherein the sensitizing dye has no

 acidic substituents and wherein a photoelectric transfer efficiency of the photoelectric transfer device is greater than about 10%.
- 2. (Cancelled)
- 3. (Original) The dye-sensitized photoelectric transfer device according to claim 1 wherein the titania nanotubes retain at least two kinds of sensitizing dyes.
- 4. (Previously presented) The dye-sensitized photoelectric transfer device according to claim 1 wherein particles of the sensitizing dye do not associate with each other.
- 5. (Original) The dye-sensitized photoelectric transfer device according to claim 1 wherein each of the titania nanotubes has a diameter from 5 nm to 80 nm.
- 6. (Previously presented) The dye-sensitized photoelectric transfer device according to claim 1 wherein the titania nanotubes are in form of an anatase crystal.
- 7. (Original) The dye-sensitized photoelectric transfer device according to claim 1 wherein the semiconductor layer and an electrolyte layer are provided between a pair of opposed electrodes.
- 8. (Previously presented) The dye-sensitized photoelectric transfer device according to claim 1 wherein the semiconductor layer and an electrolyte layer are provided between a transparent conductive substrate and a conductive substrate as a counter electrode of the transparent conductive

Application No. 10/540,629 After Final Office Action of October 30, 2006 Docket No.: S1459.70075US00

substrate to generate electric energy between the transparent conductive substrate and the conductive substrate by photoelectric transfer.

3

- 9. (Original) The dye-sensitized photoelectric transfer device according to claim 8 wherein the transparent conductive substrate is a transparent substrate having a transparent conductive film.
- 10. (Original) The dye-sensitized photoelectric transfer device according to claim 8 or 9, which is configured as a dye-sensitized solar cell.
- 11. (Currently amended) A method of manufacturing a dye-sensitized photoelectric transfer device, comprising:

providing a semiconductor layer containing titania nanotubes; and retaining a sensitizing dye with the titania nanotubes, wherein the sensitizing dye has no acidic substituents and wherein a photoelectric transfer efficiency of the photoelectric transfer device is greater than about 10%.